

**Fluitest® TP R2**

Revision date: 23.11.2017

Product code: 2RH9501

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Fluitest® TP R2

Product group: Endprodukt

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

In-vitro-Diagnostics

1.3. Details of the supplier of the safety data sheet

Company name:	Analyticon® Biotechnologies AG	
Street:	Am Mühlberg 10	
Place:	D-35104 Lichtenfels	
Telephone:	+49 (0) 6454/7991-0	Telefax: +49 (0) 6454/7991-30
e-mail:	support@analyticon-diagnostics.com	
Contact person:	Zentrale	Telephone: +49 (0) 6454/7991-0
Internet:	http://www.analyticon-diagnostics.com	

1.4. Emergency telephone number: Giftnotruf Mainz: +49 (0) 6131 / 19240**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Sodium hydroxide; caustic soda

Signal word: Danger**Pictograms:****Hazard statements**

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

**Fluitest® TP R2**

Revision date: 23.11.2017

Product code: 2RH9501

Page 2 of 8

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

copper sulphate in aqueous solution

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1310-73-2	Sodium hydroxide; caustic soda			1 - < 5 %
	215-185-5	011-002-00-6		
	Skin Corr. 1A; H314			
7758-98-7	copper sulphate			< 1 %
	231-847-6	029-004-00-0		
	Acute Tox. 4, Eye Irrit. 2, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H319 H315 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Move victim out of danger zone.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Subsequently wash off with: Polyethylene glykol 400. Remove contaminated, saturated clothing immediately.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Hazards identification: Stomach perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

Caution if victim vomits: Risk of aspiration!

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. The product itself does not burn.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

**Fluitest® TP R2**

Revision date: 23.11.2017

Product code: 2RH9501

Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

- Provide adequate ventilation.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin, eyes and clothes.
- Wear personal protection equipment.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Do not breathe gas/fumes/vapour/spray.
- Use only in well-ventilated areas.
- The floor should be leak tight, jointless and not absorbent.
- All work processes must always be designed so that the following is excluded: inhalation. skin contact. Eye contact.

Advice on protection against fire and explosion

- Usual measures for fire prevention.
- When using do not smoke.

Further information on handling

- When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place.

Advice on storage compatibility

- The product is not: Combustible. Exclude sources of ignition-no smoking

Further information on storage conditions

- Recommended storage temperature: of °C: 2 up to °C: 8
- Protect against: heat. UV-radiation/sunlight.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	-		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

- If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Fluitest® TP R2

Revision date: 23.11.2017

Product code: 2RH9501

Page 4 of 8

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Eye protection: Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374
Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

Suitable protective clothing: Lab apron.
Footwear: Chemical resistant safety shoes.

Respiratory protection

Respiratory protection necessary at: insufficient ventilation. Handling larger quantities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	blue
Odour:	characteristic

Test method**Changes in the physical state**

Melting point:	The product has not been tested.
Initial boiling point and boiling range:	The product has not been tested.

Explosive properties

The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.

Oxidizing properties

Not oxidizing.

Vapour pressure:	Corresponds to the vapour pressure of water.
------------------	--

Density:	1,01 g/cm ³
----------	------------------------

Water solubility:	completely miscible
-------------------	---------------------

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

May cause decomposition by long-term light influence.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen oxides (NO_x).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

No information available.



Fluitest® TP R2

Revision date: 23.11.2017

Product code: 2RH9501

Page 5 of 8

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7758-98-7	copper sulphate				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Irritation and etching. after ingestion:

Hazards identification: Stomach perforation.

Sensitising effects

No information available.

Carcinogenic/mutagenic/toxic effects for reproduction

No information available.

STOT-repeated exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda					
	Acute fish toxicity	LC50 45,4 mg/l	96 h	Onchorhynchus mykiss		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.6. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Fluitest® TP R2

Revision date: 23.11.2017

Product code: 2RH9501

Page 6 of 8

Waste disposal number of waste from residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
Classified as hazardous waste.

Waste disposal number of used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150106 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); mixed packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Classification code: C5
Limited quantity: LQ7
Hazard No: 80
Tunnel restriction code: E

Other applicable information (land transport)

E1
Transport category: 3

Inland waterways transport (ADN)

14.1. UN number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Classification code: C5
Limited quantity: LQ7

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)



Safety Data Sheet

Analyticon® Biotechnologies AG

analyticon

according to Regulation (EC) No 1907/2006

Fluitest® TP R2

Revision date: 23.11.2017

Product code: 2RH9501

Page 7 of 8

14.1. UN number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Limited quantity: 5 L
EmS: F-A, S-B

Other applicable information (marine transport)

Special provisions: 223
E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1824
14.2. UN proper shipping name: SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Limited quantity Passenger: 1 L
IATA-packing instructions - Passenger: 819
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 821
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E1
: Y819
Special provisions: A3

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4.

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.



analyticon

Analyticon® Biotechnologies AG

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Fluitest® TP R2

Revision date: 23.11.2017

Product code: 2RH9501

Page 8 of 8

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)